

M RPM	Gears/Sprockets						Ratio	Circ.	Spd. Loss	Raw	W/loss	
6600	14	72	30	60	12	42	36.0	1.0	0.8	3.1	2.5	
6600	14	72	30	60	14	42	30.9	1.0	0.8	3.7	2.9	
6600	14	72	30	60	15	42	28.8	1.0	0.8	3.9	3.1	
6600	14	72	30	60	16	42	27.0	1.0	0.8	4.2	3.4	
6600	14	72	30	60	17	42	25.4	1.0	0.8	4.5	3.6	
6600	14	72	30	60	18	42	24.0	1.0	0.8	4.7	3.8	
6600	14	72	30	60	19	42	22.7	1.0	0.8	5.0	4.0	
6600	14	72	30	60	20	42	21.6	1.0	0.8	5.2	4.2	
6600	14	72	30	60	22	42	19.6	1.0	0.8	5.8	4.6	
6600	14	72	30	60	25	42	17.3	1.0	0.8	6.6	5.2	
6600	14	72	30	60	28	42	15.4	1.0	0.8	7.3	5.9	
6600	14	72	30	60	29	42	14.9	1.0	0.8	7.6	6.1	

M Trq.	W Rad.	W Trq.	Trq. Loss	W Frc.	CoF	Weight	Speed
0.2	0.2	6.6	0.9	36.0	0.7	53.7	2.5
0.2	0.2	5.6	0.9	30.9	0.7	46.1	2.9
0.2	0.2	5.3	0.9	28.8	0.7	43.0	3.1
0.2	0.2	4.9	0.9	27.0	0.7	40.3	3.4
0.2	0.2	4.6	0.9	25.4	0.7	37.9	3.6
0.2	0.2	4.4	0.9	24.0	0.7	35.8	3.8
0.2	0.2	4.1	0.9	22.7	0.7	33.9	4.0
0.2	0.2	3.9	0.9	21.6	0.7	32.2	4.2
0.2	0.2	3.6	0.9	19.6	0.7	29.3	4.6
0.2	0.2	3.2	0.9	17.3	0.7	25.8	5.2
0.2	0.2	2.8	0.9	15.4	0.7	23.0	5.9
0.2	0.2	2.7	0.9	14.9	0.7	22.2	6.1